

# N420V-4

ASME B1.1


DIN 376



**Material groups**



**CHARACTERISTICS**



**Technical drawing**



**Profile sketch**



**Tool data**

| ID     | D1        | Ø d1 | Tol | P     | l1    | l2   | d2   | a   |   |      |
|--------|-----------|------|-----|-------|-------|------|------|-----|---|------|
| 142743 | UNC3/8-16 | 9.53 | 2B  | 1.588 | 100.0 | 22.0 | 7.00 | 5.5 | 3 | 8.00 |

**Product range N420V-4 UNC3/8-16 2B**

| ID     | D1         | Ø d1  | Tol | P     | l1    | l2   | d2    | a    |   |       |
|--------|------------|-------|-----|-------|-------|------|-------|------|---|-------|
| 142742 | UNC5/16-18 | 7.94  | 2B  | 1.411 | 90.0  | 20.0 | 6.00  | 4.9  | 3 | 6.50  |
| 142744 | UNC7/16-14 | 11.11 | 2B  | 1.814 | 100.0 | 19.0 | 8.00  | 6.2  | 3 | 9.30  |
| 142743 | UNC3/8-16  | 9.53  | 2B  | 1.588 | 100.0 | 22.0 | 7.00  | 5.5  | 3 | 8.00  |
| 142745 | UNC1/2-13  | 12.70 | 2B  | 1.954 | 110.0 | 24.0 | 9.00  | 7.0  | 3 | 10.80 |
| 142746 | UNC5/8-11  | 15.88 | 2B  | 2.309 | 110.0 | 30.0 | 12.00 | 9.0  | 3 | 13.60 |
| 142747 | UNC3/4-10  | 19.05 | 2B  | 2.540 | 125.0 | 33.0 | 14.00 | 11.0 | 3 | 16.60 |
| 142748 | UNC7/8-9   | 22.23 | 2B  | 2.822 | 140.0 | 36.0 | 18.00 | 14.5 | 3 | 19.50 |
| 142749 | UNC1-8     | 25.40 | 2B  | 3.175 | 160.0 | 39.0 | 18.00 | 14.5 | 4 | 22.30 |