

GWI3066VS

ASME B1.1


DC




Material groups



CHARACTERISTICS



Profile sketch



Tool data

ID	D1	Ø d1	P	l1	l2	l3	d2		
186136	UNC1/4-20	4.89	1.270	51.0	2.5	18.2	8.00	4	5.10

Product range GWI3066VS UNC1/4-20

ID	D1	Ø d1	P	l1	l2	l3	d2		
186128	UNC2-56	1.66	0.454	40.0	0.9	6.1	4.00	3	1.75
186129	UNC3-48	1.91	0.529	40.0	1.1	7	4.00	3	2.00
186130	UNC4-40	2.11	0.635	51.0	1.3	8	5.00	3	2.25
186131	UNC5-40	2.44	0.635	51.0	1.3	9.1	5.00	4	2.55
186132	UNC6-32	2.59	0.794	51.0	1.6	10.2	6.00	4	2.75
186133	UNC8-32	3.25	0.794	51.0	1.6	11.9	6.00	4	3.40
186134	UNC10-24	3.60	1.058	51.0	2.1	14	8.00	4	3.80
186135	UNC12-24	4.27	1.058	51.0	2.1	15.7	8.00	4	4.40
186136	UNC1/4-20	4.89	1.270	51.0	2.5	18.2	8.00	4	5.10
186137	UNC5/16-18	5.95	1.411	75.0	2.8	23	6.00	5	6.50
186138	UNC3/8-16	7.10	1.588	83.0	3.2	27	8.00	5	8.00
186139	UNC7/16-14	7.95	1.814	83.0	3.6	32	8.00	5	9.30
186140	UNC1/2-13	9.95	1.954	95.0	3.9	36	10.00	5	10.80