

GW3066VX

ASME B1.1

DC



Werkstoff-Gruppen



Merkmale



Profilzeichnung



Werkzeugdaten

ID	D1	Ø d1	P	l1	l2	l3	d2		
187387	UNF7/16-20	7.95	1.270	83.0	2.5	31	8.00	5	9.80

Produktgattung GW3066VX UNF7/16-20

ID	D1	Ø d1	P	l1	l2	l3	d2		
187375	UNF0-80	1.15	0.318	40.0	0.6	4.3	4.00	3	1.20
187376	UNF1-72	1.44	0.353	40.0	0.7	5.1	4.00	3	1.50
187377	UNF2-64	1.73	0.397	40.0	0.8	6	4.00	3	1.80
187378	UNF4-48	2.23	0.529	51.0	1.1	7.9	5.00	3	2.35
187379	UNF5-44	2.51	0.577	51.0	1.2	9	5.00	4	2.60
187380	UNF6-40	2.77	0.635	51.0	1.3	10	6.00	4	2.90
187381	UNF8-36	3.35	0.706	51.0	1.4	11.7	6.00	4	3.50
187382	UNF10-32	3.91	0.794	51.0	1.6	13.5	8.00	4	4.05
187383	UNF12-28	4.44	0.907	51.0	1.8	15.4	8.00	4	4.60
187384	UNF1/4-28	4.95	0.907	51.0	1.8	17.6	8.00	4	5.50
187385	UNF5/16-24	5.95	1.058	75.0	2.1	22	6.00	5	6.90
187386	UNF3/8-24	7.10	1.058	83.0	2.1	26	8.00	5	8.50
187387	UNF7/16-20	7.95	1.270	83.0	2.5	31	8.00	5	9.80
187388	UNF1/2-20	9.95	1.270	95.0	2.5	35	10.00	5	11.40