

GWI3067VS

ISO 5855


DC




Material groups



CHARACTERISTICS



Profile sketch



Tool data

| ID | D1 | Ø d1 | P | l1 | l2 | l3 | d2 | | |
|--------|---------|------|-------|------|-----|-----|------|---|------|
| 188820 | MJ3x0.5 | 2.17 | 0.500 | 51.0 | 1.0 | 9.9 | 5.00 | 4 | 2.60 |

Product range GWI3067VS MJ3x0.5

| ID | D1 | Ø d1 | P | l1 | l2 | l3 | d2 | | |
|--------|-----------|------|-------|------|-----|------|-------|---|-------|
| 188820 | MJ3x0.5 | 2.17 | 0.500 | 51.0 | 1.0 | 9.9 | 5.00 | 4 | 2.60 |
| 188821 | MJ4x0.7 | 2.84 | 0.700 | 51.0 | 1.4 | 13.3 | 6.00 | 4 | 3.40 |
| 188827 | MJ6x0.75 | 4.76 | 0.750 | 51.0 | 1.5 | 19.4 | 8.00 | 4 | 5.35 |
| 188822 | MJ5x0.8 | 3.67 | 0.800 | 51.0 | 1.6 | 16.5 | 8.00 | 4 | 4.30 |
| 188823 | MJ6x1 | 4.34 | 1.000 | 51.0 | 2.0 | 19.8 | 8.00 | 4 | 5.10 |
| 188828 | MJ8x1 | 5.95 | 1.000 | 75.0 | 2.0 | 26 | 6.00 | 5 | 7.10 |
| 188824 | MJ8x1.25 | 5.95 | 1.250 | 75.0 | 2.5 | 27 | 6.00 | 5 | 6.90 |
| 188829 | MJ10x1.25 | 7.95 | 1.250 | 83.0 | 2.5 | 33 | 8.00 | 5 | 8.90 |
| 188825 | MJ10x1.5 | 7.95 | 1.500 | 83.0 | 3.0 | 33 | 8.00 | 5 | 8.70 |
| 188830 | MJ12x1.5 | 9.95 | 1.500 | 95.0 | 3.0 | 39 | 10.00 | 5 | 10.70 |
| 188826 | MJ12x1.75 | 9.95 | 1.750 | 95.0 | 3.5 | 40 | 10.00 | 5 | 10.40 |