

RN05-2

ISO 1502

DC SWISS



CHARACTERISTICS



Profile sketch



Tool data

ID	D1	Ø d1	Tol	P	l1	l2	d2
191502	M1	1.00	6h	0.250	24.0	2.0	6.00

Product range RN05-2 M1 6h

ID	D1	Ø d1	Tol	P	l1	l2	d2
192900	M0.3	0.30	5h	0.080	24.0	0.6	6.00
192901	M0.35	0.35	5h	0.090	24.0	0.7	6.00
192902	M0.4	0.40	5h	0.100	24.0	0.8	6.00
192903	M0.5	0.50	5h	0.125	24.0	1.0	6.00
192904	M0.6	0.60	5h	0.150	24.0	1.2	6.00
192905	M0.7	0.70	5h	0.175	24.0	1.4	6.00
192906	M0.8	0.80	5h	0.200	24.0	1.6	6.00
192907	M0.9	0.90	5h	0.225	24.0	1.8	6.00
191502	M1	1.00	6h	0.250	24.0	2.0	6.00
191503	M1.2	1.20	6h	0.250	24.0	2.3	6.00
191504	M1.4	1.40	6h	0.300	24.0	2.7	6.00
191523	M1.6	1.60	6g	0.350	24.0	3.1	6.00
191524	M1.8	1.80	6g	0.350	24.0	3.4	6.00
191525	M2	2.00	6g	0.400	24.0	3.8	6.00
191526	M2.3	2.30	6g	0.400	24.0	4.3	6.00
191527	M2.5	2.50	6g	0.450	24.0	4.7	6.00

ID	D1	Ø d1	ToI	P	l1	l2	d2
191528	M2.6	2.60	6g	0.450	24.0	4.8	6.00