

TAZ40

DIN 14

DC



Caratteristiche



Disegno del profilo



Dati dell'utensile

ID	D1	Ø d1	Tol	P	l1	l2	d2		
193995	M0.6	0.60	4H	0.150	25.0	1.8	2.00	3	0.50

Famiglia di prodotti TAZ40 M0.6 4H

ID	D1	Ø d1	Tol	P	l1	l2	d2	a		
193994	M0.5	0.50	4H	0.125	25.0	1.5	2.00	0.0	3	0.41
193995	M0.6	0.60	4H	0.150	25.0	1.8	2.00	0.0	3	0.50
193996	M0.7	0.70	4H	0.175	25.0	2.1	2.00	0.0	3	0.58
193997	M0.8	0.80	4H	0.200	25.0	2.4	2.00	0.0	3	0.66
193998	M0.9	0.90	4H	0.225	25.0	2.7	2.00	0.0	3	0.74
193999	M1	1.00	4H	0.250	40.0	3.0	2.50	0.0	3	0.75
194000	M1.2	1.20	4H	0.250	40.0	3.6	2.50	0.0	3	0.95
194001	M1.4	1.40	4H	0.300	40.0	4.2	2.50	0.0	3	1.10
194002	M1.6	1.60	6H	0.350	40.0	4.8	2.50	0.0	3	1.25
194003	M1.8	1.80	6H	0.350	40.0	5.4	2.50	0.0	3	1.45
194004	M2	2.00	6H	0.400	45.0	8.0	2.80	2.1	3	1.60
194005	M2.3	2.30	6H	0.400	45.0	9.0	2.80	2.1	3	1.90
194006	M2.5	2.50	6H	0.450	50.0	10.0	2.80	2.1	3	2.05
194007	M2.6	2.60	6H	0.450	50.0	10.0	2.80	2.1	3	2.15