


Q360VS-3

ASME B18.29.1

DIN 2184-1




Material groups



CHARACTERISTICS



Profile sketch



Tool data

| ID | D1 | Ø d1 | Tol | P | l1 | l2 | l3 | d2 | a | | |
|--------|------------|------|-----|-------|------|-----|----|------|-----|---|------|
| 204650 | EG UNC4-40 | 3.67 | 3B | 0.635 | 56.0 | 6.5 | 20 | 4.00 | 3.0 | 3 | 3.05 |

Product range Q360VS-3 EG UNC4-40 3B

| ID | D1 | Ø d1 | Tol | P | l1 | l2 | l3 | d2 | a | | |
|--------|---------------|------|-----|-------|-------|------|----|-------|-----|---|------|
| 204650 | EG UNC4-40 | 3.67 | 3B | 0.635 | 56.0 | 6.5 | 20 | 4.00 | 3.0 | 3 | 3.05 |
| 204651 | EG UNC6-32 | 4.54 | 3B | 0.794 | 70.0 | 9.0 | 25 | 6.00 | 4.9 | 3 | 3.75 |
| 204652 | EG UNC8-32 | 5.20 | 3B | 0.794 | 70.0 | 9.0 | 25 | 6.00 | 4.9 | 3 | 4.45 |
| 204653 | EG UNC10-24 | 6.20 | 3B | 1.058 | 80.0 | 11.0 | 30 | 7.00 | 5.5 | 3 | 5.10 |
| 204654 | EG UNC1/4-20 | 8.00 | 3B | 1.270 | 90.0 | 12.5 | 35 | 8.00 | 6.2 | 3 | 6.70 |
| 204655 | EG UNC5/16-18 | 9.77 | 3B | 1.411 | 100.0 | 14.0 | 39 | 10.00 | 8.0 | 3 | 8.40 |