

# GWI3065VS

ASME B1.1

DC





### CHARACTERISTICS



Profile sketch



### Tool data

| ID     | D1      | Ø d1 | P     | l1   | l2  | l3  | d2   |  |  |
|--------|---------|------|-------|------|-----|-----|------|---|---|
| 206558 | UNF8-36 | 3.35 | 0.706 | 51.0 | 1.4 | 9.7 | 6.00 | 4   | 3.50  |

### Product range GWI3065VS UNF8-36

| ID     | D1        | Ø d1 | P     | l1   | l2  | l3   | d2   |  |  |
|--------|-----------|------|-------|------|-----|------|------|---|---|
| 206552 | UNF0-80   | 1.15 | 0.318 | 40.0 | 0.6 | 3.5  | 4.00 | 3   | 1.20  |
| 206553 | UNF1-72   | 1.44 | 0.353 | 40.0 | 0.7 | 4.2  | 4.00 | 3   | 1.50  |
| 206554 | UNF2-64   | 1.73 | 0.397 | 40.0 | 0.8 | 4.9  | 4.00 | 3   | 1.80  |
| 206555 | UNF4-48   | 2.23 | 0.529 | 51.0 | 1.1 | 6.4  | 5.00 | 3   | 2.35  |
| 206556 | UNF5-44   | 2.51 | 0.577 | 51.0 | 1.2 | 7.4  | 5.00 | 4   | 2.60  |
| 206557 | UNF6-40   | 2.77 | 0.635 | 51.0 | 1.3 | 8.2  | 6.00 | 4   | 2.90  |
| 206558 | UNF8-36   | 3.35 | 0.706 | 51.0 | 1.4 | 9.7  | 6.00 | 4   | 3.50  |
| 206559 | UNF10-32  | 3.91 | 0.794 | 51.0 | 1.6 | 11.1 | 8.00 | 4   | 4.05  |
| 206560 | UNF12-28  | 4.44 | 0.907 | 51.0 | 1.8 | 12.7 | 8.00 | 4   | 4.60  |
| 206561 | UNF1/4-28 | 4.95 | 0.907 | 51.0 | 1.8 | 14.4 | 8.00 | 4   | 5.50  |